

PIX

The Fastest Emerging Global Player!



TopCoat® 225 L100 - LE0
TopCoat® 225 L100 - LE0
TopCoat® 225 L100 - LE0

X-GALLANT® - HXS 3HC 2325 Lp
GALLANT® - HXS 3HC 2325 Lp
GALLANT® - HXS 3HC 2325 Lp

PIX-PowerTex - XV2® X62x22-K-1745Li
PIX-PowerTex - XV2® X62x22-K-1745Li
PIX-PowerTex - XV2® X62x22-K-1745Li

PIX-MUSCLE-XS® SPZ 640

PIX-X'act® STD S 5M 800
PIX-X'act® STD S 5M 800
PIX-X'act® STD S 5M 800

DO NOT FOLD
TWIST OR CRIMP
DO NOT FOLD
TWIST OR CRIMP
DO NOT FOLD
TWIST OR CRIMP

PIX-X'ceed® 10PJ 1800
PIX-X'ceed® 10PJ 1800
PIX-X'ceed® 10PJ 1800
PIX-X'ceed® 10PJ 1800

ANTISTATIC, OIL
& HEAT RESISTANT
ANTISTATIC, OIL
& HEAT RESISTANT
ANTISTATIC, OIL
& HEAT RESISTANT

PIX-X'tra® BX 33 / X17x840 Li
PIX-X'tra® BX 33 / X17x840 Li

ANTISTATIC, OIL
& HEAT RESISTANT
ANTISTATIC, OIL
& HEAT RESISTANT

PIX-X'set® B 100 17x2540 Li
ANTISTATIC, OIL
& HEAT RESISTANT

PIX-X^{set}-XS WRAP CONSTRUCTION BELTS



WRAPPED CLASSICAL BELTS

Product Code	Section	Top Width (mm)	Thickness (mm)	Angle (Degrees)	Standard	Rec. Min Pulley Dia (mm)	Manufacturing Range		Belt Length Factor			Length Designation
							Min	Max	Li to Li (mm)	Li to Li (mm)	Li to Li (mm)	
WST-9	9	8.0 mm	5.0 mm	40	DIN 2215-1975	40 mm	40"	175"	12	19	31	Li
WST-Z	Z	10.0 mm	6.0 mm	40	IS 2494, BS 3790, ISO 4194	50 mm	9.5"	195"	16	22	38	Li
WST-A	A	13.0 mm	8.0 mm	40	IS 2494, BS 3790, ISO 4194	71 mm	13"	357"	14	36	50	Li
WST-B	B	17.0 mm	11.0 mm	40	IS 2494, BS 3790, ISO 4194	112 mm	16"	658"	26	43	69	Li
WST-20	20	20.0 mm	13.0 mm	40	DIN 2215-1975	160 mm	35.5"	375"	31	48	79	Li
WST-C	C	22.0 mm	14.0 mm	40	IS 2494, BS 3790, ISO 4194	180 mm	31"	900"	32	56	88	Li
WST-25	25	25.0 mm	16.0 mm	40	DIN 2215-1975	250 mm	57"	900"	39	61	100	Li
WST-D	D	32.0 mm	19.0 mm	40	IS 2494, BS 3790, ISO 4194	355 mm	44.5"	900"	40	79	119	Li
WST-E	E	38.0 mm	23.0 mm	40	IS 2494	500 mm	90"	900"	53	92	145	Li

WRAPPED WEDGE BELTS

WST-SPZ	SPZ	10.0 mm	8.0 mm	40	BS 3790	63 mm	365 mm	4953 mm	13	37	50	Lp
WST-SPA	SPA	13.0 mm	10.0 mm	40	BS 3790	90 mm	576 mm	9110 mm	18	45	63	Lp
WST-SPB	SPB	17.0 mm	14.0 mm	40	BS 3790	140 mm	1000 mm	16764 mm	28	60	88	Lp
WST-19	19	19.0 mm	15.0 mm	40	DIN 7753	180 mm	2184 mm	9068 mm	25	69	94	Lp
WST-SPC	SPC	22.0 mm	18.0 mm	40	BS 3790	224 mm	1750 mm	22860 mm	30	83	113	Lp

WRAPPED NARROW BELTS

WST-3V	3V	9.7 mm	8.0 mm	40	RMA IP 22	63 mm	19.5"	190"	13	37	50	La
WST-5V	5V	15.8 mm	14.0 mm	40	RMA IP 22	140 mm	44"	654"	25	60	85	La
WST-8V	8V	25.4 mm	23.0 mm	40	RMA IP 22	335 mm	90"	900"	53	92	145	La

WRAPPED LIGHT DUTY SINGLE V-BELTS

Series	3L	4L	5L
Product Code	WST-3L	WST-4L	WST-5L
Top width (mm)	10	13	17
Thickness (mm)	6	8	10
Angle (deg)	40	40	40
Range La (inches)	10.5-176	15-357	21-239

Application: General industrial and engineering drives.

Features of PIX-X-Set-XS Wrapped Belts

- Oil Resistant
- Antistatic
- Max belt linear speed up to 30 m/sec
- Temperature Range: -18°C to +80°C
- ATEX Certified FRAS Belts are available

PIX-X^{tra}-XR RAW EDGE COGGED BELTS



RAW EDGE COGGED CLASSICAL BELTS

Product Code	Section	Top Width (mm)	Thickness (mm)	Angle (Degrees)	Standard	Rec. Min Pulley Dia (mm)	Manufacturing Range		Belt Length Factor			Length Designation
							Min	Max	Li to Li (mm)	Li to Li (mm)	Li to Li (mm)	
XST-ZX	ZX	10.0 mm	6.0 mm	36	IS 2494, BS 3790, ISO 4194	40 mm	23"	200"	16	22	38	Li
XST-AX	AX	13.0 mm	8.0 mm	36	IS 2494, BS 3790, ISO 4194	63 mm	22"	200"	14	36	50	Li
XST-BX	BX	17.0 mm	11.0 mm	36	IS 2494, BS 3790, ISO 4194	90 mm	21"	200"	26	43	69	Li
XST-CX	CX	22.0 mm	14.0 mm	36	IS 2494, BS 3790, ISO 4194	140 mm	21"	200"	32	56	88	Li

RAW EDGE COGGED WEDGE BELTS

XST-XPZ	XPZ	10.0 mm	8.0 mm	36	BS 3790	56 mm	590 mm	5117 mm	13	37	50	Lp
XST-XPA	XPA	13.0 mm	10.0 mm	36	BS 3790	71 mm	590 mm	5125 mm	21	42	63	Lp
XST-XPB	XPB	17.0 mm	14.0 mm	36	BS 3790	112 mm	600 mm	5140 mm	28	60	88	Lp
XST-XPC	XPC	22.0 mm	18.0 mm	36	BS 3790	180 mm	600 mm	5163 mm	38	75	113	Lp

RAW EDGE COGGED NARROW BELTS

XST-3VX	3VX	9.7 mm	8.0 mm	38	RMA IP 22	56 mm	24"	202"	13	37	50	La
XST-5VX	5VX	15.8 mm	14.0 mm	38	RMA IP 22	112 mm	24"	203"	28	55	85	La
XST-8VX	8VX	25.4 mm	23.0 mm	38	RMA IP 22	254 mm	90"	200"	49	96	145	La

LIGHT DUTY SINGLE V-BELTS

Series	2LX	3LX	4LX	5LX
Product Code	XST-2LX	XST-3LX	XST-4LX	XST-5LX
Top width (mm)	6	10	13	17
Thickness (mm)	4	6	8	10
Angle (deg)	38	38	38	38
Range La (inches)	24-201	24-201	24-202	24-202

Application: General industrial and engineering drives.

Features of PIX-X^{tra}-XR (Raw Edge Cogged Belts)

- Oil Resistant & Antistatic
- Max belt linear speed up to 30 m/sec
- Higher power transmission capacity than Wrapped Belts
- Superior transverse stiffness & high wear resistance
- Suitable for drives with small pulley diameters, high ambient temp & speeds
- Temperature Range: -25°C to +100°C
- ATEX Certified FRAS Belts are available

PIX-X^{ceed}-XC RIBBED / POLY V-BELTS



Product Code	Section	Thickness (mm)	Rib Pitch (mm)	Rec. Min Pulley Dia (mm)	Range Effective Length		Length Designation
					Min	Max	
*PST-NPH	PH	2.9 mm	1.60 mm	13 mm	280 mm	5080 mm	Le
*PST-NPJ	PJ	3.8 mm	2.34 mm	20 mm	280 mm	5080 mm	Le
*PST-NPL	PL	7.6 mm	4.70 mm	75 mm	500 mm	5080 mm	Le
*PST-NPM	PM	13.3 mm	9.40 mm	180 mm	950 mm	5080 mm	Le

Note: *N = Number of Ribs

Features of PIX-X^{ceed}-XC Ribbed Belts

- Oil Resistant & Antistatic
- High Power Transmission Capacity
- Temperature Range: -25°C to +100°C
- Max belt linear speed up to 50 m/sec
- Highly flexible, noise free & smooth running
- Can be used for speed ratios up to 1:30
- ATEX Certified FRAS Belts are Available

Application: For compact drives with high speed ratios, drives requiring minimum maintenance, drives in a noise sensitive environment, for serpentine drives and drives with reverse bend idlers like household appliances, work tools, machine tools etc.

PIX-X'act® - XT TIMING / SYNCHRONOUS BELTS

Features of PIX-X'act-XT Timing Belts


- High efficiency due to positive engagement between belt teeth and pulley grooves
- Free from maintenance, No re-tensioning & high tension required
- Fibre glass cord provides strength, excellent flex life & high resistance to elongation

- Exact Power Transmission
- Low noise level & longer service life
- Improved stress distribution



PIX-X'act® CT CLASSICAL TIMING BELTS

Product Code	Section	Pitch (mm)	Tooth Height (mm)	Belt Thickness (mm)	Manufacturing Range	Length Designation
TST-XL	XL	5.080	1.27	2.30	130XL - 450XL	Lp
TST-L	L	9.525	1.91	3.60	124L - 720L	Lp
TST-H	H	12.700	2.29	4.30	230H - 1700H	Lp




Note : Maximum sleeve width is available up to 450 mm



PIX-X'act® STD STD TIMING BELTS

Product Code	Section	Pitch (mm)	Tooth Height (mm)	Belt Thickness (mm)	Manufacturing Range	Length Designation
TST-S5M	S 5M	5.00	1.91	3.40	STD S 5M 375 - STD S 5M 2525	Lp
TST-S8M	S 8M	8.00	3.05	5.30	STD S 8M 378 - STD S 8M 2800	Lp




Note : Maximum sleeve width is available up to 450 mm



PIX-X'act® HTD HTD TIMING BELTS

Product Code	Section	Pitch (mm)	Tooth Height (mm)	Belt Thickness (mm)	Manufacturing Range	Length Designation
TST-5M-	5M	5.00	2.06	3.80	330 5M - 2100 5M	Lp
TST-8M-	8M	8.00	3.48	6.00	424 8M - 3600 8M	Lp
TST-14M-	14M	14.00	6.25	10.00	966 14M - 3850 14M	Lp



Note : Maximum sleeve width is available up to 450 mm

Application: Suitable for drives demanding exact power transmission such as robotic machines, textile machinery, CNC Machines, Electronic equipment such as printers, scanners, currency counting machines etc.

PIX-DuraBand® HIGH POWER BANDED BELTS

Features of PIX-DuraBand Banded Belts

- Enhanced Power Transmission capacity up to 25%
- Lesser number of belts required as compared to multiple single-belt drive
- High adhesion strength between tie band and the belts
- Eliminates changes of mismatch in length as observed in multiple single-belt drive
- Antistatic, oil and heat resistant
- ATEX certified FRAS belts are also available
- Manufactured through single stage curing process



PIX-DuraBand® XS WRAPPED BANDED BELTS (AS PER ISO 5290, ISO 5291, BS 3790 STD.)

Product Code	Section	Top Width (mm)	Thickness (mm)	Angle (Degrees)	Pitch (mm)	Manufacturing Range		Length Designation
						Min	Max	
WDB-HA	HA	13.0	10.0	40	15.9	33"	255"	Li
WDB-HB	HB	17.0	13.0	40	19.0	43"	370"	Li
WDB-HC	HC	22.0	16.0	40	25.5	47"	900"	Li
WDB-HD	HD	32.0	21.5	40	37.0	90"	900"	Li
WDB-HE	HE	38.0	27.0	40	44.5	90"	900"	Li
WDB-HZ	HZ	10.0	8.5	40	10.3	45"	174"	Li
WDB-HSPZ	HSPZ	10.0	10.0	40	12.0	1168 mm	9042 mm	Lp
WDB-HSPA	HSPA	13.0	12.0	40	15.0	914 mm	4470 mm	Lp
WDB-HSPB	HSPB	17.0	16.0	40	19.0	1702 mm	9271 mm	Lp
WDB-HSPC	HSPC	22.0	20.0	40	25.5	2184 mm	22860 mm	Lp
WDB-H3V	H3V	9.7	10.0	40	10.3	35.5"	178"	La
WDB-H5V	H5V	15.8	16.0	40	17.5	48"	660"	La
WDB-H8V	H8V	25.4	25.0	40	28.6	95"	900"	La

All Wrapped section belts such as B, C, D, E, SPC and 8V in single and banded construction can be supplied up to 1000" or 25400 mm



PIX-DuraBand® XR RAW EDGE COGGED BANDED BELTS

XDB-HAX-	HAX	13.0 mm	10.0 mm	36	15.9 mm	23.5"	200"	Li
XDB-HBX-	HBX	17.0 mm	13.0 mm	36	19.0 mm	23.5"	200"	Li
XDB-HCX-	HXC	22.0 mm	16.0 mm	36	25.5 mm	23.5"	200"	Li
XDB-HXPZ	HXPZ	10.0 mm	10.0 mm	36	12.0 mm	600 mm	5080 mm	Lp
XDB-HXPA-	HXPA	13.0 mm	12.0 mm	36	15.0 mm	600 mm	5080 mm	Lp
XDB-HXPB-	HXPB	17.0 mm	16.0 mm	36	19.0 mm	600 mm	5080 mm	Lp
XDB-HXPC-	HXPC	22.0 mm	20.0 mm	36	25.5 mm	600 mm	5080 mm	Lp
XDB-H3VX-	H3VX	9.7 mm	10.0 mm	36	10.3 mm	23.5"	200"	La
XDB-H5VX-	H5VX	15.8 mm	16.0 mm	36	17.5 mm	23.5"	200"	La

(AS PER ISO 5290, ISO 5291, BS 3790 STD.)

Application:

Best suited for drives with severe vibrations, Vertical Shaft Drives, V-flat Drives, Agricultural Drives, Stone Crushers, Heavy Duty Compressors, Generator sets, Pumps, Cold Forging Machines & Mining Equipment.

PIX - VARIABLE SPEED BELTS

Features:

- Excellent transverse rigidity and flexibility to prevent bucking at minimum diameter settings where belt stresses are greatest
- Firm gripping action in the contact areas provide positive traction for precise, immediate response
- Higher Power Transmission than regular range
- Longer service life
- Facilitates smooth running without excessive vibration
- Specific Belt Design for maximum longitudinal flexibility



PIX-X'set® vs WRAPPED VARIABLE SPEED BELTS

Product Code	Section	Angle (Degrees)	Manufacturing Range		Length Designation
			Min	Max	
WVS-17x8-	17x8	40	800 mm	1262 mm	Li
WVS-25x13/HI-	25x13 / HI	30	1080 mm	8992 mm	Li
WVS-32x15/HJ-	32x15 / HJ	34	1175 mm	8244 mm	Lp
WVS-38x18/HK-	38x18 / HK	30	1500 mm	9170 mm	Lp
WVS-45x20/HL-	45x20 / HL	30	1800 mm	8845 mm	Lp
WVS-51x20/HM-	51x20 / HM	34	1893 mm	9590 mm	Lp
WVS-58x25-	58x25	30	1930 mm	6604 mm	Lp
WVS-60x25-	60x25	30	1930 mm	6604 mm	Lp

(AS PER ISO 3410:1989 / BS 3733: 1974 STANDARDS)

NON STANDARD SIZES

Product Code	Section	Angle (Degrees)	Min	Max	Length Designation
WVS-13x11-	13x11	40	1087 mm	2057 mm	Li
WVS-15x9-	15x9	40	608 mm	6482 mm	Li
WVS-19x11-	19x11	40	1100 mm	3937 mm	Li
WVS-21x9-	21x9	40	991 mm	1930 mm	Li
WVS-22x16-	22x16	40	1727 mm	8553 mm	Li
WVS-30x12-	30x12	30	1002 mm	8604 mm	Li
WVS-33x22-	33x22	30	3915 mm	22860 mm	Li
WVS-38x23-	38x23	26	2362 mm	8966 mm	Li
WVS-40x20-	40x20	30	878 mm	6579 mm	Li
WVS-68x24-	68x24	32	2540 mm	9042 mm	Li

PIX-X'tra®-xv RAW EDGE COGGED VARIABLE SPEED BELTS



Product Code	Section	Top Width (mm)	Thickness (mm)	Angle (Degrees)	Belt Length Factor			Pitch Length (mm)	
					Li to La (mm)	Li to Lp (mm)	Li to La (mm)	Min	Max
XVS-22V-A22/1422V-	22V-A22/1422V	22.0	8.0	22	15	35	50	700	5115
XVS-30V-A22/1922V-	30V-A22/1922V	30.0	10.0	22	20	42	62	700	5125
XVS-37V-A22/2322V-	37V-A22/2322V	37.0	11.0	22	23	46	69	700	5126
XVS-30V-A26/1926V-	30V-A26/1926V	30.0	11.0	26	23	46	69	700	5126
XVS-46V-A26/2926V-	46V-A26/2926V	46.0	13.0	26	27	55	82	700	5137
XVS-51V-A26/3226V-	51V-A26/3226V	51.0	13.0	26	27	55	82	700	5137
XVS-40V-A30/2530V-	40V-A30/2530V	40.0	15.0	30	30	65	95	700	5146
XVS-51V-A30/3230V-	51V-A30/3230V	51.0	16.0	30	33	67	100	700	5147
XVS-70V-A30/4430V-	70V-A30/4430V	70.0	18.0	30	37	77	114	700	5157
XVS-64V-A36/4036V-	64V-A36/4036V	64.0	18.0	36	37	77	114	700	5157
XVS-70V-A36/4436V-	70V-A36/4436V	70.0	18.0	36	37	77	114	700	5157
XVS-76V-A36/4836V-	76V-A36/4836V	76.0	19.0	36	39	81	120	700	5161
XVS-HG-	HG	16.5	8.0	26	15	35	50	700	5115
XVS-HH-	HH	20.4	10.0	26	20	42	62	700	5125
XVS-HI-	HI	25.4	12.7	26	27	55	82	700	5135
XVS-HJ-	HJ	31.8	15.1	26	30	65	95	700	5145
XVS-HK-	HK	38.1	17.5	26	37	77	114	700	5155
XVS-HL-	HL	44.5	19.8	26	40	82	122	700	5165
XVS-HM-	HM	50.8	22.2	26	45	90	135	700	5177
XVS-HN-	HN	57.2	23.9	26	50	100	150	700	5185
XVS-HO-	HO	63.5	25.4	26	53	106	159	700	5192

(AS PER RMA IP 25/1991, ISO 3410 (E) / IS: 8777-1978 STANDARDS)

RAW EDGE COGGED VARIABLE SPEED BELTS (NON-STANDARD SECTIONS)

Product Code	Thickness (mm)	Manufacturing Range (Inches)		Length Designation
		Min	Max	
XVS-5.0 (REC/REP)-	5.0 (REC/REP)	23.5	86	Li
XVS-8.0 (REC/REP)-	8.0 (REC/REP)	24.0	200	Li
XVS-9.0 (REC/REP)-	9.0 (REC/REP)	24.0	200	Li
XVS-10.0 (REC/REP)-	10.0 (REC/REP)	24.0	200	Li
XVS-11.0 (REC/REP)-	11.0 (REC/REP)	24.0	200	Li
XVS-12.0 (REC/REP)-	12.0 (REC/REP)	24.0	200	Li
XVS-13.0 (REC/REP)-	13.0 (REC/REP)	27.0	200	Li
XVS-14.0 (REC/REP)-	14.0 (REC/REP)	27.0	200	Li
XVS-15.0 (REC/REP)-	15.0 (REC/REP)	27.0	200	Li
XVS-16.0 (REC/REP)-	16.0 (REC/REP)	27.0	200	Li
XVS-17.0 (REC/REP)-	17.0 (REC/REP)	35.0	200	Li
XVS-18.0 (REC/REP)-	18.0 (REC/REP)	35.0	200	Li
XVS-19.0 (REC/REP)-	19.0 (REC/REP)	35.0	200	Li
XVS-20.0 (REC/REP)-	20.0 (REC/REP)	35.0	200	Li
XVS-21.0 - 30.0 (REC)-	21.0 - 30.0 (REC)	63.0	200	Li
XVS-20.0 - 22.0 (REP)-	20.0 - 22.0 (REP)	63.0	200	Li

Note: These belts can be manufactured with Top Width ranging from 5 mm to 82 mm & Angle: 22° to 60°

Applications:


For use on variable speed pulley drives requiring exact speed control and maximum range of speed changes. Ideal for recreational equipment, agricultural applications and machine tools.

PIX - RAW EDGE PLAIN & LAMINATED BELTS



PIX-X'tra®-XP

Raw Edge Plain Belts



PIX-X'tra®-XL

Raw Edge Laminated Belts

Standards, Dimensions & Product Range: Same as Raw Edge Moulded Cogged Belts

PIX - SPECIAL CONSTRUCTION BELTS

Features:

- Longer service life
- Excellent adhesion between top profile and the belt
- Application specific designed belts
- Designed for applications where power transmission and conveying of material is done simultaneously

PIX-ECHELON®-XS



Product Code	Section	Top Width (mm)	Thickness (mm)	Height of Pattern (mm)	Manufacturing Range		Length Designation
					Min	Max	
WPO-B-	B (17x14)	17	14	3.0	85"	658"	Li
WPO-B-	B (17x16)	17	16	5.0	85"	658"	Li
WPO-A-	A (13x13)	13	13	5.0	48"	356"	Li
WPO-37 x 25-	37 x 25	37	25	5.0	116"	375"	Li

For Food Grain & Ceramic Tiles Industry



PIX-TEXTURA®-XS

WHC-B-	B (17x17)	17 mm	17 mm	6 mm	42"	658"	Li
WHC-C-	C (22x20)	22 mm	20 mm	6 mm	66"	900"	Li

For Ceramic Tiles and General Industries



PIX-CERAMICA®-XS

WPG-B-	B (17x22)	17 mm	22 mm	11 mm	85"	357"	Li
WPG-B-	B (17x26)	17 mm	26 mm	15 mm	66"	356"	Li
WPG-B-	B (17x21)	17 mm	21 mm	10 mm	42"	79"	Li
WPG-C-	C (22x25)	22 mm	25 mm	11 mm	73"	320"	Li

For Ceramic Tiles Industry



PIX-EXTRACTOR®-XS

WP7-37-	37(37x25)	37 mm	25 mm	7 mm	4064 mm	8890 mm	Lp
WP7-D-	D (32x26)	32 mm	26 mm	7 mm	142"	633"	Li

For Carrot Harvesting Machines, Horticultural Industry

PIX-FRAS® FIRE RESISTANT ANTISTATIC BELTS



PIX-FRAS®-XS

Wrapped Belts

PIX-FRAS®-XR

Raw Edge Belts

PIX-FRAS®-XC

Ribbed / Poly Belts

Features:

- Fire Resistant
- Antistatic
- ATEX Certified

Product Range:

- Entire range in Wrapped, Raw Edge and Ribbed / Poly Belts
- Banded Belts are also available in Wrapped and Raw Edge Construction

PIX-BRUTE® HIGH POWER BELTS



PIX-BRUTE®-XS

Wrapped Belts

PIX-BRUTE®-XR

Raw Edge Belts

Features:

- High power transmission up to 20-30%
- Longer belt service life
- Reduced number of belts are required
- Lesser belt deformation in comparison to regular belt
- Lower drive cost

Product Range:

- Entire range in Wrapped and Raw Edge Constructions
- Banded Belts are also available

PIX-THERMAL® HIGH TEMPERATURE BELTS



PIX-THERMAL®-XS

Wrapped Belts

Temp. Range: -25°C to +100°C

PIX-THERMAL®-XR

Raw Edge Belts

Temp. Range: -35°C to +130°C

PIX-THERMAL®-XC

Ribbed / Poly Belts

Temp. Range: -35°C to +130°C

PIX-THERMAL®-XT

Timing Belts

Temp. Range: -40°C to +150°C


Features:

- Very high temperature resistant
- Longer service life
- Crack & damage free in high temperature application
- Higher power transmission capacity in comparison to regular belts

Product Range:

- Entire range in Wrapped, Raw Edge, Poly/ Ribbed and Timing Belt Constructions
- Banded Belts are also available in Wrapped and Raw Edge Construction

PIX-Duo® DOUBLE SIDED BELTS



PIX-Duo®-XS HEXAGONAL BELTS

Product Code	Section	Top Width (mm)	Thickness (mm)	Angle (Degrees)	Rec. Min Pulley Dia (mm)	Manufacturing Range (Inches)		Length Designation
						Min	Max	
WDS-AA	AA	13.0	10.0	40	80	46	254	Li
WDS-BB	BB	17.0	14.0	40	125	40	660	Li
WDS-CC	CC	22.0	17.0	40	224	73	900	Li
WDS-25	25	25.0	22.0	40	280	88	900	Le

PIX Duo®-XR DOUBLE COG BELTS

Top Width (mm)	30-80		
Thickness (mm)	14-20	20-24	24-30
Angle	22-32°		
Range Li (mm)	1000-2000	1600-2000	2050-4800

Features of PIX-Duo Belts:

- Absolutely flexible
- Transmits power from both the sides
- This special construction allows belt to be used in "serpentine drive" system

PIX-Duo®-XC DOUBLE SIDED POLY V-BELTS

Sections:

DPK: 2 to 13 ribs. Range: 1195 mm to 3105 mm

DPL: 2 to 11 ribs. Range: 1200 mm to 3105 mm

PIX-HARVESTER® AGRICULTURAL BELTS



PIX-HARVESTER®-XS

Wrapped Belts

PIX-HARVESTER®-XR

Raw Edge Belts

PIX-HARVESTER®-XC

Ribbed / Poly Belts

Features of PIX-Harvester Belts

- Specially designed for application with outside idlers
- More flexible, suitable for small pulley diameters
- Higher power transmission than regular belts
- Excellent performance under variable load conditions

Product Range:

- Standard product range & OEM Parts in Wrapped, Raw Edge and Ribbed / Poly Belts
- Banded Belts are also available in Wrapped and Raw Edge Construction

PIX-MUSCLE®-XS MUSCLE BELTS



Features:

- 30-35% more power transmission
- Maintenance free
- No elongation
- REACH complaint, Eco friendly
- Longer service life, less down time, reduced drive cost
- Space saver belts
- Reduced wear

Product Range: Z, A, B, C, SPZ, SPA, SPB, SPC, 3V, 5V Sections

PIX-GREEN POWER® HALOGEN FREE BELTS



Features:

- Trouble free and efficient performance without any harmful emissions
- Eco-friendly belt
- REACH and RoHS compliant
- Smooth-running operation
- Halogen-free
- Helps maintain pollution free environment

Product Range: All Wrapped Belts in Classical, Narrow & Wedge sections

PIX-ASYMMETRA® ASYMMETRIC BELTS



Top Width (mm)	Thickness (mm)			Manufacturing Range	Length Designation
19.0 mm	10.0 mm	18°	2°	1005 mm	La
16.0 mm	9.0 mm	18°	2°	695 mm	La
19.0 mm	10.0 mm	18°	2°	740 mm	La
19.0 mm	8.0 mm	18°	2°	660 mm	La
19.0 mm	10.0 mm	18°	2°	665 mm	La

Application: Golf cart, snow mobiles, Minibikes, Material Handling & Industrial Equipment

PIX-TIMING POLY BELTS



Features:

- Suitable for multi-shaft transmission with reversed rotary directions of pulleys
- Anti static, oil and heat resistant
- Noise free transmission
- Operating temperature range -25°C to +100°C

Range: Entire timing belt range with PK & PL poly sections

Applications: Flour & rice mills, Food grain industries

Note: Available in Kevlar / Glass cord constructions

PIX-TopCoat® TOP COAT BELTS



Shore Hardness: 43 ± 3 (Red Colour) Shore Hardness: 50 ± 3 (Magenta Colour)

Shore Hardness: 57 ± 3 (Coral Colour) Shore Hardness: 67 ± 3 (Black Colour)

PIX-TopCoat®
Timing Belts
Product Range (Lp): 570 - 2000 mm
Top Width: As per requirement

PIX-TopCoat®
Poly / Ribbed Belts
Product Range (Le): 700 - 2000 mm
No of Ribs: PJ: Up to 36 ribs
 PK: Up to 24 ribs
 PL: Up to 18 ribs



Shore Hardness: 43 ± 3 (Red Colour) Shore Hardness: 50 ± 3 (Magenta Colour)

Shore Hardness: 57 ± 3 (Coral Colour) Shore Hardness: 67 ± 3 (Black Colour)

Features:

- PIX Top Coat Belt is having profile top rubber specific to applications
- The profile top rubber provides excellent cushioning coupled with extra elasticity
- Excellent flexibility of PIX Top Coat Belt prevents cracking or tearing while application
- Premium friction suitable for providing proper support to contact material
- Belts are designed with abrasion resistance properties
- Top Profile Thickness: 1.5, 3, 6, 8 & 10mm

Temperature Range: -18° to +80°C

Application: FFS (Form-fill & seal) machine, bakeries, paper & printing, soaps & cosmetics, cables drawing, plastic tube drawing, bottling plants etc.

Note:

1. Belt selection should strictly be done on the basis of temperature, top coat hardness & application.
2. Availability of particular size in product range to be cross checked before placing order.

PIX-GALLANT® HEAVY DUTY HIGH POWER BELTS



Features:

- More power transmission capacity
 - Up to 40% for PIX Gallant single belts
 - Up to 55% for PIX Gallant banded belts
- Specially treated outer tough cover reduces sidewall wear
- Kevlar corded to withstand sudden shear forces at peak loads
- Belt is designed to exhibit excellent durability, strength, abrasion & wear resistant
- Unique performance under heavy shocks & impulse loads
- Low heat generation even at very high speed
- Best solution for compact drives as lesser number of belts are required
- "Fit it Once". No re-tensioning required
- One single branding that combines all the major features & fit for every robust application

Product Range: Z, A, B, C, SPZ, SPA, SPB, SPC, 3V, 5V Sections

Applications: Agriculture, forestry, mining, construction & manufacturing machinery

PIX-PowerTex® TEXTILE MACHINERY BELTS



Features:

- Designed to meet high power transmission requirement of textile spinning mills of up to 60 kW
- Developed for spinning mills to operate at spindle with very high speeds of up to 20000 RPM
- Higher power transmission capacity
- Excellent performance & customer satisfaction by giving energy saving solutions in textile spinning application

Product Range: Range as per request

Application: Textile spinning machines

PIX-DUO-N-XS® WRAP DOUBLE SIDED NOTCHED BELTS



Sections	Top Width (mm)	Thickness (mm)	Angle (Degrees)	Manufacturing Range (Inches)		Length Designation
				Min	Max	
N-22X30	22.0	30.0	40	153	900	Li

Note: Other Hexagonal Notched Belt Sections are available on request.

Application: Textile industry

Features:

- Special notched design suitable for drying / textile machines
- Special notched profile belt offers excellent flexibility & extended life in operation
- Designed to cater application with large center distances & serpentine drives

PIX-DryCover® DRY COVER BELTS



Features:

- Suitable for drives having clutch applications.
- Designed for applications where contamination is not accepted.
- Available in Polyester and Aramid cord constructions

Application: Chemical, pharmaceuticals, food industry etc.

PIX-LawnMaster® LAWN MOWER BELTS



Features:

- High tensile strength, non-extensibility, high resistance to shock loads
- High resistance to wear and tear, reduced slippage while clutching
- Able to withstand high level of reverse flexing
- High resistance to Oil, Heat and cracking

Product Range: 3L, 4L, 5L & other OEM parts